

D Series



Reflectance Dependent Models – Analog

Model Number	Fiber Optic Diameter		Total Range		Near Side Range		Far Side Range		Down load
	inch	mm	inch	mm	inch	mm	inch	mm	PDF
D6	0.006	0.15	0.040	1	0.008	0.20	0.032	0.80	Click
D12	0.012	0.30	0.080	2	0.010	0.25	0.070	1.75	Click
D20	0.020	0.51	0.050	1.15	0.005	0.12	0.045	1.15	Click
D21	0.021	0.51	0.080	2	0.010	0.25	0.070	1.75	Click
D47	0.047	1.19	0.200	5	0.012	0.30	0.175	4.70	Click
D63	0.063	1.60	0.120	3	0.006	0.15	0.112	2.85	Click
D64	0.064	1.60	0.240	6	0.010	0.25	0.230	5.80	Click
D100	0.100	2.54	0.400	10	0.016	0.40	0.380	9.60	Click
D125	0.125	3.18	0.600	15	0.016	0.40	0.575	14.60	Click
D169	0.169	4.32	0.800	20	0.020	0.50	0.770	19.50	Click
D170	0.170	4.32	1.200	30	0.035	0.90	1.150	29.10	Click
D171	0.171	4.32	2.000	50	0.375	9.50	1.600	40.50	Click
D240	0.240	6.10	3.000	76	0.550	14.00	2.400	62.00	Click