

DMS-RC Series



Reflectance Compensated Models – Digital									
Model Number	Fiber Optic Area		Total Span		Operating Range		Best Resolution		Down load
	inch	mm	inch	mm	inch	mm	inch	mm	PDF
DMS-RC19	Ø 0.02	Ø 0.5	0.03	0.76	0.03	0.76	0.03	0.1	Click
DMS-RC20	Ø 0.02	Ø 0.5	0.065	1.65	0.065	1.65	0.05	0.08	Click
DMS-RC25	0.025 x 0.125	0.64 x 3.2	0.03	0.76	0.03	0.76	0.03	0.05	Click
DMS-RC32	Ø 0.032	Ø 0.8	0.08	2	0.080	2	0.08	0.5	Click
DMS-RC60	Ø 0.06	Ø 1.5	0.16	4	0.16	4	0.16	0.18	Click
DMS-RC62	0.062 x 0.125	1.6 x 3.2	0.08	2	0.08	2	0.10	0.25	Click
DMS-RC63	0.063 x 0.125	1.6 x 3.2	0.16	4	0.16	4	0.20	0.64	Click
DMS-RC90	0.090 x 0.187	2.3 x 4.8	0.35	9	0.35	9	0.35	0.4	Click
DMS-RC100	Ø 0.100	Ø 2.5	0.20	5.1	0.20	5.1	0.24	0.55	Click
DMS-RC125	Ø 0.125	Ø 3.18	0.20	9	0.35	9	22	0.8	Click
DMS-RC171	Ø 0.171	Ø 4.3	0.5	12.7	0.50	12.7	0.59	0.65	Click
DMS-RC190	0.190 x 0.187	4.83 x 4.75	1.00	25.4	1.00	20	1.0	0.65	Click
DMS-RC290	Ø 0.293	Ø 7.4	1.60	41	1.60	34	1.4	2.5	Click