

RC Series



Reflectance Compensated Models – Analog									
Model Number	Fiber Optic Area		Total Span		Operating Range		Sensitivity		Down load
	inch	mm	inch	mm	inch	mm	mv/mil	mv/μm	PDF
RC19	Ø 0.020	Ø 0.5	0.030	0.76	0.030	0.76	225	9	Click
RC20	Ø 0.020	Ø 0.5	0.065	1.65	0.065	1.65	120	5	Click
RC25	0.025 x 0.125	0.6 x 3.2	0.030	0.76	0.030	0.76	250	10	Click
RC32	Ø 0.032	Ø 0.81	0.080	2	0.080	2	75	3	Click
RC60	Ø 0.060	Ø 1.52	0.125	3.2	0.125	3.2	55	2.2	Click
RC62	0.062 x 0.125	1.57 x 3.18	0.080	2	0.080	2	73	3	Click
RC63	0.063 x 0.125	1.57 x 3.18	0.160	4	0.160	4	45	1.8	Click
RC90	0.090 x 0.187	2.29 x 4.75	0.350	9	0.350	9	22	0.8	Click
RC100	Ø 0.100	Ø 2.54	0.200	5.1	0.200	5.1	23	0.9	Click
RC125	Ø 0.125	Ø 3.18	0.200	9.0	0.350	9.0	22	0.8	Click
RC171	Ø 0.171	Ø 4.3	0.500	12.7	0.500	12.7	12	0.5	Click
RC190	0.190 x 0.187	4.83 x 4.75	1.000	25.4	0.787	20	12	0.5	Click
RC290	Ø 0.293	Ø 7.44	1.600	41	1.340	34	5.6	0.22	Click